

Spencer Turbine



Spencer Turbine marka ürünler Özhat tarafından Türkiye'ye paralel ithalat yöntemi ile ithal edilmekte ve siz değerli müşterilerimize en hızlı şekilde teslim edilmektedir. Spencer Turbine ürünlerinden websitemizde ürün numarası yer almasa bile teklif isteyiniz ; en kısa sürede teklifimiz tarafınıza ulaştırılacaktır.

Spencer Turbine Ürün Listesi

Referans	Tanım
02X42	Weiblicher Adapter
02X42 2" TUBE X2"NPTX107LG	Adapter,Femal, Expanded Ends
04R23	fitting
20R20	Coupling Reducing
20S20,2 1/8 IN	FITTING, TUBE, Ärmel, Schrumpf-
20T20	LEITUNGEN 20ft (wird in Stücke geschnitten, von 3MT für Sendungen.)
25L45	(2 1/2" OD 45 Elbow (standard radius),Material Z/G)
25T20	(2 1/2" OD Tubing (600 mm long), Material Z/G)
40L90	90°
40T20	hose 7500 mm
FIL90336	Filtern
B24205A	no 270023 Spare parts for turbine three wheels plus keys and intermediaries seals
CPL90194	(2 1/2" Male Hose Repair Coupling)
MODEL NO: 30207A1	4-Bearing Overhung(4-BOH) , differential pressure 3 PSIG, Casing Carbon Steel,Inlet Pressure 14.7 PSIA , Impellers Fabricated Aluminium, Inlet Temperature 70 F , Shaft Carbon Steel , Gas Composition Air, Stationary Internals Carbon Steel , Specific Gravity 1.000 , Baseplate Carbon Steel K-Factor (Cp/Cv)1.395 , Shaft Seals Vellomodium and Felt, Blower Speed 2900 RPM, Inlet 8"Dia.125/150#ANSI Drill Flg.Outlet 8"Dia .125/150#ANSI Drill Flg ,Motor Specifications 30Hp, 190/380 Volts , 3 Phase ,50 Hertz 2900 RPM , Enclosure TEFC
VLV90100	(Inlet Valve for 2" ID Hose - 2" MPT, Material:Ni plate)
VLV90107	(Inlet Valve for 2 1/2" ID Hose - 2 1/2" MPT,Material Ni plate)
20L90, 2 1/8 IN	ELLBOGEN, 90 GRAD
22F82	FITTING, ROHR, ADAPTER, WEIBLICHER KOHLENSTOFFSTAHL
20L45	ELLBOGEN, 45 GRAD
29T02	ANSCHLUSS ROHRADAPTER
30T200	TUBING 20ft
60T20	TUBING 20ft
BLR90150	Gebläse
VLV90102	Einlassventil, 2" FPT, Locking Type

Referans	Tanım
22F20-ZG	2" x 2" FPT ADAPTER, GALV-
29T02-ZG	2-1 / 8x2-1 / 8 90 ° Tys - ZG
VLV90083	Einlassventil, 2 in ML THRD - NO FLG
BRG90113	Bearing