

## CE-TL-...

Telescopic tri-oval insulating stick, extended length 2.0 m, max voltage 75 kV, K universal fitting

### Application:

- Insulating stick dedicated for works from ground with light mechanical constraint.
- Fuse disconnecting/re-connecting.
- Voltage detection.
- Light maneuvers, whereas CE-TL-2 may be also used to operate earthing and short-circuiting equipment.

### Features:

- Insulating telescopic stick according to ASTM F 1826 ("Live Line and Measuring Telescoping Tools").
- Dielectric withstand voltage: 100 kV / 30 cm (1").
- Tube: composite tube made of glass-reinforced plastic (GRP).
- Foam-filled tip section:

1. Additional safety by sealing the inner tube, preventing water from entering.
2. Strengthens the stick.

- End-fitting: serrated universal (K).
- Tri-oval section shape:

1. Optimized ergonomics providing better hand grip for greater handling force.
2. Higher rigidity when extended enabling excellent handling control.
3. User friendlier by extending and folding the telescopic stick.

- Button: square-shaped for reinforced resistance.
- Heavy duty rubber boot.
- Stick stopper to prevent inadvertent section extension during transport.
- Maintenance: easy replacement thanks to take-apart sections.
- Delivered with maneuver hook [11-5306-2](#) (except CE-TL-2-015-K and CE-2-TL-020-K).

