

5.1. Fluid & electric 电气

Position	Item	Brand	Type	Additional information
Upper Tool	Temperature control Forward	日东	4P-A	
	Temperature control Return	日东	4S-A	
	Pneumatic Air	日东	3S-A	
	Vacuum	Storz	SIZE D (DIN14306)	
	Electric	Harting	Type: 19 30 024 0267 Type: 09 33 024 2602. Type: 09 33 000 6105. Type: 09 33 000 6118.	
Lower Tool	Temperature control Forward	日东	4P-A	
	Temperature control Return	日东	4S-A	
	Pneumatic Air	日东	3S-A	
	Vacuum	Storz	SIZE C (DIN14307)	
	Electric	Harting	Type: 19 30 024 0267. Type: 09 33 024 2602. Type: 09 33 000 6105. Type: 09 33 000 6118.	



Manufacture, process and supply plastic,
insulation and rubber products to industry

www.par-group.co.uk
Preston (Head office): +44 (0) 1257 248369:
Manchester: +44 (0) 1706 363790

Storz Coupling x Female BSP

AL



Brass or aluminium storz coupling to female BSP.

Also available: In stainless steel (subject to availability). Please replace the BR suffix with SS if stainless steel is required. Eg SF20SS. 3 lug options may also be available upon request, please enquire.

Product Code (Alu)	Product Code (Brass)	Storz Size	KA (mm)	BSP Female
SF1	SF1BR	25 (D)	31	1/2"
SF2	SF2BR	25 (D)	31	3/4"
SF3	SF3BR	25 (D) = DIN 14306	31	1"
SF4	SF4BR	32	44	1"
SF5	SF5BR	32	44	1 1/4"
SF6	SF6BR	38	52	1 1/2"
SF7	SF7BR	38	52	2"
SF8	SF8BR	52 (C)	66	1"
SF9	SF9BR	52 (C)	66	1 1/4"
SF10	SF10BR	52 (C)	66	1 1/2"
SF11	SF11BR	52 (C) = DIN 14307	66	2"
SF12	SF12BR	52 (C)	66	2 1/2"
SF13	SF13BR	65	81	2"
SF14	SF14BR	65	81	2 1/2"
SF15	SF15BR	75 (B)	89	2"
SF16	SF16BR	75 (B) = DIN 14308	89	2 1/2"
SF17	SF17BR	75 (B)	89	3"
SF18	SF18BR	90	105	3"
SF19	SF19BR	100	115	4"
SF20	SF20BR	110 (A)	133	4"
SF21	SF21BR	110 (A) = DIN 14309	133	4 1/2"
SF22	SF22BR	125	148	5"
SF23	SF23BR	150	160	6"
SF24	SF24BR	165	188	6"
SF25	SF25BR	165	188	7"
SF26	SF26BR	205	220	8"

Product Code (Alu)	Product Code (Brass)	Storz Size	KA (mm)	BSP Female
SF27	-	250	278	10"
SSP	-	Storz Spanner	-	-

Related Products

