



Kühlgeräte / Cooling units
Serie RAM Anbau Edelstahl

Die Kühlgeräte-Serie RAM mit Edelstahlhaube (AISI 304) ist für den Chemie-, Pharma-, Food and Beverage- und den geschützten Outdoor-Bereich mit hohen Umgebungstemperaturen bis zu +55°C konzipiert. Serienmäßig ist ein elektronischer Temperaturregler mit Türkontaktschleife und potentialfreiem Störmeldekontakt verbaut. Geräte ab 1.000W Kühlleistung besitzen eine integrierte Kondensatverdunstung. Selbstverständlich verfügen alle Geräte über zwei voneinander getrennte Kreisläufe: IP54/IP34.



- LED Easy-Control
- Aufgeschäumte Dichtung
- Kondensatverdunstung ab 1.000W Kühlleistung serienmäßig
- **CE** **UL** **US** Varianten
- Gängige Typen ab Lager lieferbar

The cooling units series RAM with Inox cover (AISI 304) are specially developed for chemical-, pharmacy-, food & beverage-industry and for the protected outdoor usage with high temperatures up to +55°C. An electronic temperature controller including a door-switch control and alarm-signal is built in as standard. Units with 1.000W and higher cooling power are equipped with integrated condensate dissipators. Of course all units are designed with two separated air-circuits to prevent intrusion of dust to the cabinet: IP54/IP34.



- LED Easy-Control
- Applied seal
- Condensate dissipator from 1.000W cooling power as standard
- **CE** **UL** **US** Versions
- Common units on stock

Serie RAM Anbau Edelstahl	Type Model	Tu Ta	Nutzkühlleistung Cooling Power	Spannung Voltage	Abmessungen Dimensions
Bestell-Nr./Order-No.		bis °C	W (L35-L35)	V, Hz	B x H x T (mm)
20.RAMX.03XX.0901	RIKLMFUH03021LT ¹⁾	55	320	230, 1~, 50/60	280 x 500 x 180
20.RAMX.03XQ.0901	RIKLMFU0302100T	55	330	230, 1~, 50/60	280 x 284 x 248
20.RAMM.05XX.0901	RIKLMFUH05021LM ¹⁾	55	520	230, 1~, 50/60	280 x 595 x 170
20.RAMX.05XX.0903	RIKLMFUH05042LT ¹⁾	55	520	380/400/440/460/480, 2~, 50/60	280 x 595 x 220
20.RAMX.08XX.0901	RIKLMFUH08021LT ¹⁾	55	830	230, 1~, 50/60	280 x 630 x 270
20.RAMX.08XX.0903	RIKLMFUH08042LT ¹⁾	55	830	380/400/440/460/480, 2~, 50/60	280 x 630 x 270
20.RAMM.08XQ.0901	RIKLMFUH080210M	55	880	230, 1~, 50/60	580 x 350 x 270
20.RAMM.08XQ.0903	RIKLMFUH080420M	55	880	380/400/440/460/480, 2~, 50/60	580 x 350 x 270
20.RAMM.10XX.0901	RIKLMFUH10021LM	55	1.020	230, 1~, 50/60	400 x 950 x 195
20.RAMM.10XX.0903	RIKLMFUH10042LM	55	1.020	380/400/440/460/480, 2~, 50/60	400 x 950 x 195
20.RAMX.15XX.0901	RIKLMFUH15021LT	55	1.420	230, 1~, 50/60	400 x 950 x 237
20.RAMX.15XX.0903	RIKLMFUH15042LT	55	1.420	380/400/440/460/480, 2~, 50/60	400 x 1050 x 237
20.RAMX.15XX.0907	RIKLMFUH15043LT	55	1.420	400/440, 3~, 50/60	400 x 1050 x 237
20.RAMX.20XX.0901	RIKLMFUH20021LT	55	1.960	230, 1~, 50/60	400 x 950 x 237
20.RAMX.20XX.0903	RIKLMFUH20042LT	55	1.960	380/400/440/460/480, 2~, 50/60	400 x 1050 x 237
20.RAMX.20XX.0907	RIKLMFUH20043LT	55	1.960	400/440, 3~, 50/60	400 x 1050 x 237
20.RAMX.30XX.0901	RIKLMFUH30021LT	55	2.800	230, 1~, 50	500 x 1100 x 345
20.RAMX.30XX.0907	RIKLMFUH30043LT	55	2.800	380/400/440/460/480, 3~, 50/60	500 x 1100 x 345
20.RAMX.40XX.0907	RIKLMFUH40043LT	55	4.000	380/400/440/460/480, 3~, 50/60	500 x 1100 x 345
20.RAMX.60XX.0907	RIKLMFUH60043LT	55	5.600	400/460, 3~, 50/60	550 x 1400 x 400

¹⁾ Optional mit integrierter Kondensatverdunstung lieferbar
Integrated condensate dissipator as option

