BUNN[®]

BrewWISE® Single Soft Heat® **DBC®** Brewer

ITEM#		
PROJECT		

DATE



Model Single SH DBC with 1.5 gallon SH Servers

(servers sold separately) Dimensions: 35.8" H x 9.3" W x 21.2" D (90.9cm H x 23.6cm W x 53.8cm D)

Features

BrewWISE Brewing System

- Brews 11.4 gallons (43.2 litres) of perfect coffee per hour.
- Brews ½, 1, or 1½ gallon (1.9, 3.8 or 5.7 litre) batches.
- Stores individual coffee and flavor profiles using adjustable water volume, bypass percentage, pulse brew, and pre-infusion timing.
- Operate any combination of BrewWISE equipment error-free with wireless brewer-grinder interface via Smart Funnel®.
- Reduce accidents with safety features that decrease hot splashes from funnel, eliminate brewing when funnel or server is not present.
- Troubleshoot all switches and electrical components from the front panel with advanced diagnostic service tools.
- Consistently brew perfect coffee using Digital Brewer Control with pulse brew.
- Simplify installation and calibration by creating your own recipe cards and dedicated funnels with the BrewWISE Recipe Writer using your PC (Windows® compatible).
- International electrical configurations available.

For current specification sheets and other information, go to www.bunn.com.

Related Products

Easy Clear® EQHP-10 Product No.: 39000.0004

Easy Clear® EQHP-10L Product No.: 39000.0001



Single/Dual Filter Pack

Product No.: 20138.0000 Packed per case: 500

Dimensions: 51/4" Base x 41/4" Sidewall 13.3 cm Base x 10.8 cm Sidewall



BrewWISE® Recipe Writer (BRW)

Product No.: 34444.0000 (120V)

Dimensions:

23/16" H x 63/8" W x 91/2" D 5.56 cm H x 16.2 cm W x 24.1 cm D



Recipe Card

Product No.: 34447.0000

• Program a recipe to be used on brewer or grinder.



Ad Card

· Program a message to appear on the brewer's display.



G9-2T DBC

Product No.: 33700.0000

G9-2TA DBC

Intl. Product No.: 33700.0005

· Grinder holds 6 pounds each of regular and decaf or specialty beans



Product No.: 34448.0000



Model

Agency Listing

Single SH DBC

G9-2T DBC

SH Server and Stands



CUL US LISTED NSF.

Dimensions & Specifications


Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Capacity	Cubic Measure	Shipping Weight	Cord Attached
Single SH DBC	33600.0000	120/240	17.5	4000	4100	11.4 gal./hr.	7.9 ft ³	59 lbs.	No
Single SH DBC [†]	33600.0001	120/240	17.5	4000	4100	11.4 gal./hr.	7.9 ft ³	59 lbs.	No
Single SH DBC*	33600.0013	120/240	17.5	4000	4100	11.4 gal./hr.	7.9 ft ³	59 lbs.	No
G9-2T DBC	33700.0000	120	9.4	n/a	1128	n/a	5.9 ft ³	67 lbs.	Yes
SH Server(1.5 gal.)	27850.0001	n/a	n/a	n/a	n/a	1.9 gal.	2.4 ft ³	17 lbs.	n/a
SH Server*(1.5 gal.)	27850.0004	n/a	n/a	n/a	n/a	1.9 gal.	2.4 ft ³	17 lbs.	n/a
1SH Stand	27825.0000	120	.8	n/a	90	1 SH Server	1.2 ft ³	13 lbs.	Yes
1SH Stand*	27825.0004	120	.8	n/a	90	1 SH Server	1.2 ft ³	13 lbs.	Yes
2SH Stand	27875.0000	120	1.5	n/a	180	2 SH Servers	2.1 ft ³	22 lbs.	Yes
2SH Stand*	27875.0003	120	1.5	n/a	180	2 SH Servers	2.1 ft ³	22 lbs.	Yes

^{*}Models have black decor. †Model has funnel lock system. Note: Soft Heat® Brewers and Servers are boxed and shipped separately. **Brewing capacity:** based upon incoming water temp of 60°F (140°F rise).

Electrical: Brewer is 3-wires plus ground service rated 120/240V, single phase, 60Hz.

Grinder is 2-wires plus ground service rated 120V, 60Hz, circuit required, ¾ HP motor.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with $\frac{1}{4}$ " male fitting.



Bunn-O-Matic® Corporation - 1400 Stevenson Drive Springfield, Illinois 62703 • 800-637-8606 • 217-529-6601 • Fax 217-529-6644 • www.bunn.com

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.