
SH06



Dimensional Drawing





SH06-FR-SR-MD-06-XI

5	Air preparation unit, 1/4" connections, -20°C to +135°C					Model Code
FR	R Filter regulator					Model Type
	SR Self relieving			relieving	7	Self/Non Relieving Drain option Output Press Range
.		MD	Manual drain, 20 bar maximum inlet pressure			
		0		6 0.2 - 6 bar output range		
				XI	5 Micron filter element	Filter Element
					NPT connections	Connections
					I/8" Gauge port	Gauge port option
					Allen key adjustment	Adjustment option
					Regular drain screw	Drain screw option
					No Brackets	Brackets
6 -FR	-FR -SR -MD -06 -XI					Model Number

This is a bespoke datasheet. For further details on the complete range, please refer to catalogue: Models SH and SC Series Air Preparation Units

Accuracy of informat

Accuracy of information We take care to ensure that product information in this catalogue is reasonably accurate and up-to-date. However, our products are continually developed and updated so to ensure accurate and up-to-date information please effect to the product catalogue issues list on our web site or contact a member of our sales team.

When selecting a product, the applicable operating system design must be considered to ensure safe use. The products function, material compatibility, adequate ratings, correct installation, operation and maintenance are the responsibilities of the system designer and user. Quality Assurance All Biold products are manufactured to a most stringent QA programme to ensure that every product will give optimum performance and realibility. Wa ent with dra party certified to BS EN ISO 9001:2008. Functional test certificate, letter of conformity and copies of original mill certificates, providing total transability are available on request, to BS EN 10204.31 where available. We neareve the right to malke changes



www.bifold.co.uk