

## BH-ALB 200K

Pressed steel fixed castor, heavy duty design, with top plate fitting, heavy duty wheel, with Blickle Besthane® polyurethane tread, with aluminium wheel centre

EAN 4047526266301

ID 854793

Customs tariff number 87169090



### Bracket: BH series

- pressed steel, zinc-plated, blue-passivated, Cr6-free
- heavy fork and top plate

### Wheel: ALB series

- tread: high-quality polyurethane elastomer Blickle Besthane®, hardness 92 Shore A, colour brown, non-marking, non-staining
- wheel centre: die-cast aluminium, colour silver grey

### Other features:

- high chemical resistance to many aggressive substances
- operating temperature: -20 °C to +70 °C, temporarily up to +90 °C, reduced load capacity over +40 °C



### Technical data:

Wheel Ø (D)	☉	200 mm
Wheel width	⊥	50 mm
Load capacity at 4 km/h	⚖	800 kg
Load capacity (static)	⚖	2,000 kg
Bearing type	⦿	ball bearing
Total height (H)	Ⓢ	245 mm
Plate size	📏	140 x 110 mm
Bolt hole spacing	🔩	105 x 75–80 mm
Bolt hole Ø	🔩	11 mm
Temperature resistance min		-20 °C
Temperature resistance max		70 °C
Tread and tyre hardness		92 Shore A
Unit weight	⚖	2.8 kg
Non-marking	✓	
Electrically conductive	✗	
Antistatic	✗	
Corrosion-resistant	✗	
Heat-resistant	✗	
Non-staining	✓	
Tread hydrolysis-resistant	✓	
Suitable for autoclaves	✗	
Suitable for machine washing	✗	

### Tread and tyre hardness

■■■■■□ 92 Shore A

### Rolling resistance

■■■■■ excellent

### Wear resistance

■■■■■ excellent

### Operating noise / floor surface preservation

■■■■□ good

